


RA-20GM

03 & 04 TYPE



外形尺寸/ Appearance Size



unit:mm

齒輪箱馬達轉矩 & 速度/ Gear Motor Torque & Speed

減速比 Reduction ratio	1/10	1/13	1/18	1/29	1/42	1/52	1/67	1/80	1/99	1/120	1/150	1/179	1/225	1/275	1/350	1/430	1/549	1/689	1/794	1/866
12V 定格扭力 Rated torque (kgf-cm)	0.16	0.20	0.25	0.41	0.51	0.62	0.81	0.86	1.10	1.30	1.50	1.77	1.80	1.80	1.80	1.80	1.80	1.80	1.80	1.80
12V 定格轉速 Rated speed (rpm)	655	525	364	226	159	129	100	84	67	56	45	37	31	25.5	20.5	16.6	13.1	10.5	9.3	8.6
24V 定格扭力 Rated torque (kgf-cm)	0.16	0.20	0.25	0.41	0.51	0.62	0.81	0.86	1.10	1.30	1.50	1.77	1.80	1.80	1.80	1.80	1.80	1.80	1.80	1.80
24V 定格轉速 Rated speed (rpm)	720	580	403	250	176	142	110	93	74	62	49.5	41	34	28.5	23	18.5	15	12	10.5	9.2
軸心迴轉方向 Rotation direction	CW		CCW		CW			CCW			CW			CCW						
長度 Length (L)	16.5			20			21.8			25.3										

馬達單體型式/ Motor Data

定格電壓 Rated volt (V)	定格扭力 Rated torque (gf-cm)	定格轉速 Rated speed (rpm)	定格電流 Rated current (A)	無負荷轉速 No load speed (rpm)	無負荷電流 No load current (A)	定格出力 Rated output (W)	重量 Weight (g)
12	22	6700	≤0.2	8000	≤0.05	1.5	32
24	22	7400	≤0.11	9000	≤0.03	1.7	32

馬達單體特性/ Motor Characteristics

